



# Stainless Steel Electrical Griddle

## Table Top

IEC  
Manufactured to comply with  
International Safety Standards  
IEC = International  
Electrical Commission  
IEC 335-1  
IEC 60335-2-38:2003



EG 1750




EG 3000




EG 3500




EG 5250




Side View




Front View




Side View




Front View



Side View



Front View



Front View

## Free Standing




EG 3000FS



EG 3500FS




EG 5250FS




Side View




Front View



Side View



Front View



Front View

- Stainless steel body.
- Temperature range 50°C to 320°C.
- 1, 2 to 3 tubular heaters of 1750 watt each.

- 9mm / 12mm thick, flat polished steel griddle plate.
- Removable stainless steel grease drip pan with drain holes.

	EG 1750	EG 3000	EG 3500	EG 5250	EG 3000FS	EG 3500FS	EG 5250FS
Hot Plate Size (mm)	395 x 333 x 9	600 x 330 x 12	600 x 415 x 12	900 x 415 x 12	600 x 330 x 12	600 x 415 x 12	900 x 415 x 12
Machine Dimension (mm)	400 x 455 x 280	600 x 455 x 288	600 x 600 x 400	900 x 600 x 400	600 x 455 x 930	600 x 600 x 930	900 x 600 x 930
Machine Weight (kg)	17	26	41	57	31	43	61
Packing Dimension (mm)	540 x 460 x 320	660 x 540 x 320	774 x 660 x 405	953 x 770 x 405	660 x 540 x 320	774 x 660 x 405	953 x 770 x 405
Rated Voltage (V)	220 ~ 240	220 ~ 240	220 ~ 240	380 ~ 415	220 ~ 240	220 ~ 240	380 ~ 415
Rated Wattage (W)	1,750	3,000	3,500	5,250	3,000	3,500	5,250
Frequency (Hz)	50 / 60	50 / 60	50 / 60	50 / 60	50 / 60	50 / 60	50 / 60
Phase	1	1	1	3	1	1	3
Packing Vol (m <sup>3</sup> )	0.05	0.11	0.21	0.30	0.11	0.21	0.30